



SPE-150/WS

Order No.: 10.1620

EUR 22,90

RRP*

PRODUCTINFOS

Flush-mount full range speakers, 15 W

- Dual cone
- Slimline design with fixed metal grille
- Suitable for mounting into ceilings, walls and car doors

TECHNICAL SPECIFICATIONS

Impedance (Z) 4Ω

Operating voltage -

Frequency range 100-12,000 Hz

Resonant frequency (fs) -

Rec. crossov. frequ. (fmax.)

(12 dB/oct.)



Power rating (P_{RMS}) -

Peak music power output (P_{MAX}) 30 W

Sensitivity 89 dB/W/m

Max. rated SPL -

Max. voltage -

Radiation angle -

Suspension compl. (Cms) -

Moving mass (Mms) -

Mech. Q factor (Qms) -

Electr. Q factor (Qes) Total Q factor (Qts) -

Equivalent volume (Vas) -

DC resistance (Re)

Force factor (BxL) -

Voice coil induct. (Le)

Voice coil diameter -

Voice coil former -

Linear excursion (X_{MAX}) -

Eff. cone area (Sd)

Magnet weight -

Magnet diameter -

Mounting cutout Ø 120 mm

Mounting depth 34 mm

Mounting hole diameter -

Hole spacing X-axis -

Hole spacing Y-axis -

Dimensions Ø 153 mm x 45 mm

Outside diameter -

Width -

Height -

Depth -

Protective class

Admiss. ambient temp. -

Weight 500 g

Sales unit

Type of speaker 130







* Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.