



EDL-620

Order No.: 16.2590

EUR 32,90

RRP *

PRODUCTINFOS

PA ceiling speaker

- 100 V line technique via audio transformer with power taps
- Extra high maximum tapping power
- For a ceiling thickness from 5 to 22 mm
- Full range speaker, type 180
- Robust metal version (basket and protective grille)

TECHNICAL SPECIFICATIONS

Impedance (Z)	-
Operating voltage	100 V
Frequency range	100-20,000 Hz
Resonant frequency (fs)	-

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Power rating (P_{RMS})	20/10/5 W
Peak music power output (P_{MAX})	-
Sensitivity	-
Max. rated SPL	-
Max. voltage	-
Radiation angle	-
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	-
Voice coil former	-
Linear excursion (X_{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	-
Mounting cutout	Ø 180 mm
Mounting depth	50 mm
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	Ø 200 mm x 65 mm
Outside diameter	-
Width	-
Height	-
Depth	-
Protective class	-
Admiss. ambient temp.	-
Weight	0.9 kg
Sales unit	-
Type of speaker	180

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.