



EDL-430/WS

Order No.: 16.2370

EUR 149,90

RRP *

PRODUCTINFOS

Top-quality PA ball speaker,

with a perfect omnidirectional sound radiation.

- 100 V line technique
- Speaker configuration of particularly high-quality
- Extensive reflector design
- High-quality sound, also suitable for radiating music
- White ABS cabinet
- 150 cm connection cable with canopy

TECHNICAL SPECIFICATIONS

Impedance (Z)

Operating voltage

Frequency range	80-15,000 Hz
Resonant frequency (fs)	
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	
Power rating (P _{RMS})	20/10/5 W
Peak music power output (P _{MAX})	
Sensitivity	92 dB/W/m
Max. rated SPL	
Max. voltage	
Radiation angle	
Suspension compl. (Cms)	
Moving mass (Mms)	
Mech. Q factor (Qms)	
Electr. Q factor (Qes)	
Total Q factor (Qts)	
Equivalent volume (Vas)	
DC resistance (Re)	
Force factor (BxL)	
Voice coil induct. (Le)	
Voice coil diameter	
Voice coil former	
Linear excursion (X _{MAX})	
Eff. cone area (Sd)	
Magnet weight	
Magnet diameter	
Mounting cutout	-
Mounting depth	-
Mounting hole diameter	
Hole spacing X-axis	
Hole spacing Y-axis	
Dimensions	Ø 250 mm
Outside diameter	
Width	
Height	
Depth	
Protective class	
Admiss. ambient temp.	
Weight	2.2 kg

Sales unit

Type of speaker -

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.